

## **turbo<sup>®</sup> II Precleaner** *Guarantee*

Maradyne Corporation warrants the **TURBO<sup>®</sup> Precleaner** spinner, (bearing assembly and rotor) for LIFE. Additionally Maradyne Corporation warrants the **TURBO<sup>®</sup> Precleaner** to be of adequate material and good workmanship to satisfactorily perform all functions which are defined and limited by the Maradyne product specification.

The company's obligations under this warranty are limited to replacement without charge for parts or complete units which the company deems to be defective. Time limitations on replacement of components (Other than the Spinner Assembly) will be within (2) years from the date of purchase or 3000 hours of use, whichever occurs first.

Maradyne Corporation will not assume transportation or other charges involved in such replacement. This warranty does not apply to units damaged by abuse, neglect or misuse, nor does it cover consequential damages.

### **SPINNER LIFETIME WARRANTY**

Fill out the following information and keep for your records. For parts and service, return the entire unit to your local dealer or to: **turbo<sup>®</sup> Precleaner, 4540 West 160th Street, Cleveland, Ohio 44135-2629.**

DATE PURCHASED \_\_\_\_\_ SERIAL NO. \_\_\_\_\_ MODEL NO. \_\_\_\_\_

DEALER'S NAME \_\_\_\_\_

DEALER'S ADDRESS \_\_\_\_\_

### **PRECLEANER INSTALLATION INSTRUCTIONS**

1. Remove the rain cap from the air intake pipe.
2. If the diameter of the intake pipe is smaller than the opening in the base of the precleaner, use plastic rings to adapt the precleaner to the pipe.
3. When placing the precleaner on the air intake pipe, make sure it is set all the way down so the slots in the base are completely covered.
4. Tighten the clamp.
5. The turbo II Precleaner must be installed at least 12" below the top of the exhaust pipe to prevent intake of harmful exhaust gases.

Your **turbo<sup>®</sup> Precleaner** is now ready for operation.

Although the **turbo<sup>®</sup> Precleaner** requires no periodic maintenance, it should be checked occasionally to make sure that foreign materials have not plugged intake area or exhaust port area. Accessory pre-screens are available to protect your **turbo<sup>®</sup> Precleaner** from large airborne materials.

NOTE: Since dry type filters and oil bath type filters are quite different in regards to the allowable amount of air intake restriction, we recommend that a vacuum gauge be used to ensure that a **turbo<sup>®</sup> Precleaner** does not cause excessive restriction (at top engine R.P.M.) when installed on an oil bath type filter.

**turbo<sup>®</sup> Precleaner**

A MARADYNE CORPORATION

4540 West 160th Street  
Phone: (216) 362-0755  
email@turboprecleaner.com

Cleveland, Ohio 44135-2629  
Fax: (216) 362-0799  
www.turboprecleaner.com